

<b>LAD</b>			
Type	<b>H52</b>	<b>IK42</b>	<b>K42</b>
Pitch	9.0mm	10.0mm	7/16" (11.1mm)
Number of shuttles	520	420	420
Spool diameter	230mm	250mm	250mm
Applicable twine			
Nylon mono	0.20 – 0.40 mm dia.	0.25 – 0.43 mm dia.	0.28 – 0.52 mm dia.
Nylon multi.	235T/3 – 235T/18 (210d/3 – 210d/18)	235T/4 – 235T/21 (210d/4 – 210d/21)	235T/6 – 235T/27 (210d/6 – 210d/27)
Mesh range (in stretch)	14 – 400mm	16 – 400mm	17 – 400mm
Production speed	Up to 24 r.p.m.	Up to 24 r.p.m.	Up to 24 r.p.m.

Type	<b>L36</b>	<b>M32</b>	<b>NO26</b>
Pitch	1/2" (12.7mm)	9/16" (14.2mm)	11/16" (17.4mm)
Number of shuttles	365	320	260
Spool diameter	250mm	250mm	250mm
Applicable twine			
Nylon mono	0.32 – 0.62 mm dia.	0.36 – 0.70 mm dia.	0.40 – 0.90 mm dia.
Nylon multi.	235T/6 – 235T/42 (210d/6 – 210d/42)	235T/9 – 235T/60 (210d/9 – 210d/60)	235T/12 – 235T/90 (210d/12 – 210d/90)
Mesh range (in stretch)	22 – 400mm	24 – 400mm	28 – 400mm
Production speed	Up to 22 r.p.m.	Up to 22 r.p.m.	Up to 22 r.p.m.

Type	<b>P21</b>		
Pitch	7/8" (22.2mm)		
Number of shuttles	210		
Spool diameter	250mm		
Applicable twine			
Nylon mono	0.52 – 1.10 mm dia.		
Nylon multi.	235T/18 – 235T/120 (210d/18 – 210d/120)		
Mesh range (in stretch)	36 – 400mm		
Production speed	Up to 22 r.p.m.		

Model LAD Specification